



STANDARD ROTATION
 PORT A PRESSURIZED - CCW
 PORT B PRESSURIZED - CCW
 STD DRILLS USE CCW

NOTES:
 1) MOTORS COME WITH A J-310 KEY.

FLG	QTY	PART NO	DESCRIPTION
4	1	J-5307	RING - CHAR LYNN ADAPTOR, JIFFY TAP
3	2	J-281	SCREW DRIVE #4 X 1/4" ROUND HEAD 18-8 SS.
2	1	J-289	NAMEPLATE, HYD MOTOR
1	1	B-3.6-R	MOTOR, CHAR-LYNN SERIES H 101-1756-009 (.79 GEROTOR)

LIMITS ON DIMENSIONS UNLESS OTHERWISE SPECIFIED		2-PL DECIMAL ± .01 3-PL DECIMAL ± .005 FRACTIONAL ± 1/64 ANGULAR ± 1/2°		AAA PRODUCTS INTERNATIONAL 7114 Harry Hines Blvd Dallas, TX 75235
DRAWN: RMckenna	DATE: 8/5/2012	CHECKED: KWaite	DATE: 10/9/2012	
SCALE: None	SHEET: 1 OF 1	RELEASED: HWomack	DATE: 10/9/2012	
TITLE: B-SERIES MOTOR ASSEMBLY, 8.9 CU. IN. PER REV., JIFFY TAP & DRILL			PART NO.: B-3.6	REV.:

THE INFORMATION CONTAINED WITHIN THIS DOCUMENT IS PROPRIETARY TO AAA PRODUCTS AND MAY NOT BE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT

D:\Engineering\Inventory Files\Internal Drawings\Motor\B-3.6.dwg