



DRILL .098 (#40), DEPTH 1/4  
2-PLACES

PORT A

PORT B

STANDARD ROTATION  
PORT A PRESSURIZED - CW  
PORT B PRESSURIZED - CCW  
STD DRILLS USE CCW

CCW

NOTES:  
1) MOTORS COME WITH A J-310 KEY.

FLG	QTY	PART NO	DESCRIPTION
4	1	J-5307	RING - CHAR LYNN ADAPTOR, JIFFY TAP
3	2	J-281	SCREW DRIVE #4 X 1/4" ROUND HEAD 18-8 SS.
2	1	J-289	NAMEPLATE, HYD MOTOR
1	1	B-6-R	MOTOR, CHAR-LYNN SERIES H 101-1006-009 (1-1/4 GEROTOR)

LIMITS ON DIMENSIONS  
UNLESS OTHERWISE SPECIFIED  
2-PL DECIMAL ± .01  
3-PL DECIMAL ± .005  
FRACTIONAL ± 1/64  
ANGULAR ± 1/2°

**AAA PRODUCTS INTERNATIONAL**  
7114 Harry Hines Blvd  
Dallas, TX 75235

DRAWN: RMckenna	DATE: 8/5/2012	CHECKED: KWaite	DATE: 10/9/2012
SCALE: None	SHEET: 1 OF 1	RELEASED: HWomack	DATE: 10/9/2012

TITLE: <b>B-SERIES MOTOR ASSEMBLY, 14.1 CU. IN. PER REV., JIFFY TAP &amp; DRILL</b>	PART NO.: <b>B-6</b>	REV.:
--	-------------------------	-------

THE INFORMATION CONTAINED WITHIN THIS DOCUMENT IS PROPRIETARY TO AAA PRODUCTS AND MAY NOT BE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT

D:\Engineering\Inventory Files\Internal Drawings\Hyd Motor\B-6.dwg