	4	3	▼	2		1
	PING AFTER INSTALLATION 23					es in gasket as shown.
в			POSITION GASKET TO SEAL PILOT H ON SIDE 'B' AS SHOWN.	IOLE ALIGN PILOT HOLE AND ON SIDE 'A' AS	SHOWN. BLOCK AND ROTATE 18	DT PRESSURE, REMOVE PIGGY BACK 0°. LEAVE GASKET AS SHOWN. REMOVE ECT SUPPLY PRESSURE - 160 PSI MAX. B
				25 1 V 24 1 V	N-115 NAMEPLATE, BLANK, FOR HE,KE,RR,D,CR, -81 SCREW, 8-32 X 5/16, SOCKET SET, FULL D	PP,SR,SS VALVES NOG POINT L, SOCKET PIPE PLUG W/LOCTITE RED VIBRA-SEAL
				21 1 V 20 1 V 19 1 V 18 4 V		CATOR PIN
₽				16 1 P 15 1 A 14 1 V 13 1 0	IX3 PIN, SPOOL OVERRIDE, 303 STAINLESS, 1 EC3-5 END CAP, INDICATOR PIN, WIPER CAVITY Y-38T-11 CLASSIC SOLENOID - STANDARD, COMPLI -85 O-RING, BUNA-N, 70 DURO, AS-010, (REF S3 SPRING - MANUAL OVERRIDE, "CLASSIC" OP-3 OVERRIDE, PUSH PIN, 303 STAINLESS, 1/	6061-T6, 1/4" & 3/8" VALVE TE OPER, TAPPED EXH., 120/60 1/4 X 3/8 X 1/16), CLASSIC OVRD SOLENOID
	9 8 7			11 4 V 10 1 P 9 1 P 8 1 S		" & 3/8" VALVES , 1/4" & 3/8" VALVE CTR, 1/4" & 3/8" VALVE
	6 SIDE 'B'			6 4 V 5 1 P 4 1 P 3 3 E	-614 SCREW, 10-24 X 1-3/4", SOCKET HEAD CA EC3 END CAP, PILOT, 380 AL, 1/4" & 3/8" VALI EC3-18 ENDCAP, SPACER, DETENT, SOLENOID, 60 CG3 GASKET - END CAP, 1/4" & 3/8" VALVE -39 O-RING, VITON, STD BODY, 1/4" & 3/8" V	P
A		SECTION A-A	18 SIDE 'A'	FLG QTY	3-6E BODY - SOLID, PIGGY BACK, ANODIZED, : PART NO DESCRIPTION LIMITS ON DIMENSIONS 2-PL DECIMAL ± .01 JUNIESE	AAA PRODUCTS
	5 4 3 2 1 NOTES: 1) ALWAYS GIVE VALVE MODEL AND PART NUMBI	VIEW FROM 3 PORT SIDE		D DERATOR VOLTAGES S	OTHERWISE SPECIFIED FRACTIONAL ± 1/64 ANGULAR ± 1/2" RAWN: RMCKenna DATE: 3/3/2025 CALE: 1:1 SHEET: 1 0F 1	PINCULCIS PILA Harry Hines Blvd PILA Harry Harry Harry Harry Hines Blvd
	2) FOR DIFFERENT VOLTAGES OTHER THAN 120/ LISTED IN TABLE BELOW. REFERENCE AY-38T DR 3) LUBRICATE DETENT BALL, SPRING AND STUD. 4	60, REPLACE SOLENOID OPERATOR WITH OPERATO AWING FOR REPLACEMENT COILS.	$ \boxed{[b]_{\uparrow}}_{(FR)(P)(FA)}$	SR30PTKQ 12VDC AY-38T-5 SR30PTKQ 24VDC AY-38T-8 SR30PTKQ 240/60 AY-38T-17	ITLE: 3/8" SIDE PORT, SNGL SOL, 2 P DTNT, PLT RTRN, CLASSIC, 120, PUSH OVRD, TPD VENT, INDC' E INFORMATION CONTAILED WITHIN THIS DOCUMENT IS PF THOUT PRIOR WRITTEN CONSENT	/60, SR3OP1KQ