-	4	3	\mathbf{A}	2		1
В	PING AFTER INSTALLATION (23)		PILOT HOLE POSITION GASKET TO SEAL PILOT HOLE ON SIDE 'B' AS SHOWN.	ALIGN PILOT HOLE AND CENTER ON SIDE 'A' AS SHOWN.	ALIGN HOLES CUTOUT FOR EXTERNAL PILOT BLOCK AND ROTATE 180°.	O O O O O O O O O O O O O O O O O O O
J			4 ₽₽ }	27 2 V-212 26 1 AN-115 25 1 V-81 24 1 V-19 23 1 V-21 22 1 DS3 21 1 V-14	SCREW, #2 X 3/16 DRIVE, TYPE U, OVAL HEAT NAMEPLATE, BLANK, FOR HE,KE,RR,D,CR,PP,SI SCREW, 8-32 X 5/16, SOCKET SET, FULL DOG PLUG, 1/8-27 NPT, 7/8 TAPER, FLUSH SEAL, SC SCREW, 1/4-20 X 3/16, SOCKET SET, CUP PDI SPRING - DETENT, 1/4* & 3/8* VALVE BALL, CHROME STEL 3/16 DJA, GRADE 25, FC	N, STAINLESS STEEL R,SS VALVES POINT CXCET PIPE PLUG W/LOCTITE RED VIBRA-SEAL IT
₽		12 13 14 15 SOLEI OPER		20 1 V-119 19 1 V-78 18 4 V-38 17 1 PIK3 16 1 PEC3-5 15 1 AY-38T-11 14 1 V-85	RING,CIRCULAR PUSH ON TYPE FOR INDICATO U-CUP, 1/2 X 1/4 X 1/8, NITRILE SCREW, 10-24 X 3/4, SOCKET HEAD CAP PIN, SPOOL OVERRIDE, 303 STAINLESS, 1/4" & END CAP, INDICATOR PIN, WIPER CAVITY, 600 CLASSIC SOLENOID - STANDARD, COMPLETE (O-RING, BUNA-N, 70 DURO, AS-010, (REF 1/4	X 7/8" VALVES 1-76, 1/4" & 3/8" VALVE DPER, TAPPED EXH., 120/60
	9			13 1 OS3 12 1 OP3 11 4 V-1 10 1 PB3-3E 9 1 PBG3-1 8 1 S3R 7 1 PBS3-13	SPRING - MANUAL OVERRIDE, "CLASSIC" SOLE PIN - MANUAL OVERRIDE, 1/4" & 3/8" VALVES SCREW, 10-24 X 2, SOCKET HEAD CAP ADAPTOR - SINGL SOL., W/OVERRIDE, 1/4" & 3 GASKET - PIGGY BACK, SINGLE SOLENOID, 1/- SPOOL - SOLID, STANDARD, 2 POS, CLSD CTR, STUD - POS. A & C. DETENT, SOLENOID OPER	/8" VALVES 1" & 3/8" VALVE 1/4" & 3/8" VALVE
А	G SIDE 'B'			6 4 V-614 5 1 PEC3 4 1 PEC3-18 3 3 ECG3 2 6 V-39 1 1 B3-6E FLG QTY PART NO	SCREW, 10-24 X 1-3/4", SOCKET HEAD CAP END CAP, PILOT, 380 AL, 1/4" & 3/8" VALVE ENDCAP, SPACER, DETENT, SOLENOID, 6061-1 GASKET - END CAP, 1/4" & 3/8" VALVE O-RING, VITON, STD BODY, 1/4" & 3/8" VALVE BODY - SOLID, PIGGY BACK, ANODIZED, 3/8" DESCRIPTION	S C C C C C C C C C C C C C C C C C C C
	5 4 3 2 1 NOTES:	SECTION A-A VIEW FROM 3 PORT SIDE 20	(B) (A) (B) (A) (4 2	U		AAA PRODUCTS INTERNATIONAL 7114 Harry Hines Blvd Dallas, TX 75235 KED: KWaite DATE: 3/2/2025
	1) ALWAYS GIVE VALVE MODEL AND PART NUMBER WHE 2) FOR DIFFERENT VOLTAGES OTHER THAN 120/60, REP LISTED IN TABLE BELOW. REFERENCE AY-38T DRAWING 3) LUBRICATE DETENT BALL, SPRING AND STUD. 4	PLACE SOLENOID OPERATOR WITH OPERATOR	D T SR30 51 3 (FE) (P) (FA) SR30 SR30	ART NO REPLACE OPERATOR TKQ 12VDC AY-38T-5 TKQ 24VDC AY-38T-5 DTNT, TKQ 240/60 AY-38T-17 LCKNG 2	SIDE PORT, SNGL SOL, 2 POS PLT RTRN, CLASSIC, 120/60 OVRD, TPD VENT, INDCTR P ION CONTAINED WITHIN THIS DOCUMENT IS PROPR A WRITTEN CONSENT	j, SR3OTKQ bi IN iii