


ALIGN PILOT HOLE AND CENTER CUTOUT ON BOTH SIDES.



ALIGN HOLES IN GASKET AS SHOWN.  
(FOR EXTERNAL PILOT PRESSURE, REMOVE PIGGY BACK BLOCK AND ROTATE 180°. LEAVE GASKET AS SHOWN. REMOVE 1/8" PLUG AND CONNECT SUPPLY PRESSURE - 160 PSI MAX.)

NOTES:  
1) ALWAYS GIVE VALVE MODEL AND PART NUMBER WHEN ORDERING PARTS.  
2) FOR DIFFERENT VOLTAGES OTHER THAN 120/60, REPLACE SOLENOID OPERATOR WITH OPERATOR LISTED IN TABLE BELOW. REFERENCE AY-38L DRAWING FOR REPLACEMENT COILS.

|     |     |           |   |
|-----|-----|-----------|---|
| 21  | 2   | V-212     | SCREW, #2 X 3/16 DRIVE, TYPE U, OVAL HEAD, STAINLESS STEEL            |
| 20  | 1   | AN-115    | NAMEPLATE, BLANK, FOR HE,KE,KD,RR,D,CR,PP,SR,SS VALVES                |
| 19  | 4   | V-1       | SCREW, 10-24 X 2, SOCKET HEAD CAP                                     |
| 18  | 2   | V-81      | SCREW, 8-32 X 5/16, SOCKET SET, FULL DOG POINT                        |
| 17  | 1   | V-19      | PLUG, SOCKET PIPE 1/8" NPT (#601-3 PITTSBURG PLUG PART #.)            |
| 16  | 1   | PEC3-5    | END CAP, INDICATOR PIN, WIPER CAVITY, 6061-T6, 1/4" & 3/8" VALVE      |
| 15  | 1   | PIK3      | PIN, SPOOL OVERRIDE, 303 STAINLESS, 1/4" & 3/8" VALVES                |
| 14  | 1   | V-78      | U-CUP, 1/2 X 1/4 X 1/8, NITRILE                                       |
| 13  | 1   | V-119     | RING,CIRCULAR PUSH ON TYPE FOR INDICATOR PIN                          |
| 12  | 2   | AY-38L-11 | CLASSIC SOLENOID, 120/60, W/DUST EXCLUDER                             |
| 11  | 2   | V-85      | O-RING, BUNA-N, 70 DURO, AS-010, (REF 1/4 X 3/8 X 1/16), CLASSIC OVRD |
| 10  | 2   | OS3       | SPRING - MANUAL OVERRIDE, "CLASSIC" SOLENOID                          |
| 9   | 2   | OP3       | PIN - MANUAL OVERRIDE, 1/4" & 3/8" VALVES                             |
| 8   | 1   | PB3-4E    | ADAPTOR - DBL SOL., W/OVERRIDE, 1/4" & 3/8" VALVES                    |
| 7   | 1   | PBG3      | GASKET - PIGGY BACK, DOUBLE SOLENOID, 1/4" & 3/8" VALVE               |
| 6   | 1   | S3R       | SPOOL - SOLID, STANDARD, 2 POS, CLSD CTR, 1/4" & 3/8" VALVE           |
| 5   | 1   | SEC3-1    | END CAP, NON-VENTED, 380 AL, 1/4" & 3/8" VALVES                       |
| 4   | 8   | V-38      | SCREW, 10-24 X 3/4, SOCKET HEAD CAP                                   |
| 3   | 2   | ECG3      | GASKET - END CAP, 1/4" & 3/8" VALVE                                   |
| 2   | 6   | V-39      | O-RING, VITON, STD BODY, 1/4" & 3/8" VALVES                           |
| 1   | 1   | B2-6E     | BODY - SOLID, PIGGY BACK, ANODIZED, 1/4" SIDE PORT VALVE              |
| FLG | QTY | PART NO   | DESCRIPTION   |

LIMITS ON DIMENSIONS  
UNLESS OTHERWISE SPECIFIED  
2-PL DECIMAL ± .01  
3-PL DECIMAL ± .005  
FRACTIONAL ± 1/64  
ANGULAR ± 1/2°

**AAA PRODUCTS INTERNATIONAL**  
7114 Harry Hines Blvd  
Dallas, TX 75235

|   |                 |                   |                 |
|---|-----------------|-------------------|-----------------|
| DRAWN: RMckenna   | DATE: 4/19/2020 | CHECKED: KWaite   | DATE: 4/19/2020 |
| SCALE: 1 : 1  | SHEET: 1 OF 1   | RELEASED: HWomack | DATE: 4/19/2020 |
| TITLE:<br><b>1/4" SIDE PORT, DBL SOL, 2 POS, SOL RTRN, CLASSIC SOL, 120/60, LCKNG OVRD, EXCLDR, THD PIN</b> |                 | PART NO.:         | REV.:           |
|   |                 | <b>SS2OLK</b>     |                 |

THE INFORMATION CONTAINED WITHIN THIS DOCUMENT IS PROPRIETARY TO AAA PRODUCTS AND MAY NOT BE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT