


ALIGN PILOT HOLE AND CENTER CUTOUT ON BOTH SIDES.



ALIGN HOLES IN GASKET AS SHOWN.  
(FOR EXTERNAL PILOT PRESSURE, REMOVE PIGGY BACK BLOCK AND ROTATE 180°. LEAVE GASKET AS SHOWN. REMOVE 1/8" PLUG AND CONNECT SUPPLY PRESSURE - 160 PSI MAX.)

#### NOTES:

- 1) ALWAYS GIVE VALVE MODEL AND PART NUMBER WHEN ORDERING PARTS.
- 2) FOR DIFFERENT VOLTAGES OTHER THAN 120/60, REPLACE SOLENOID OPERATOR WITH OPERATOR LISTED IN TABLE BELOW. REFERENCE AY-38T DRAWING FOR REPLACEMENT COILS.

|     |     |           |   |
|-----|-----|-----------|---|
| 17  | 2   | V-212     | SCREW, #2 X 3/16 DRIVE, TYPE U, OVAL HEAD, STAINLESS STEEL            |
| 16  | 1   | AN-114    | NAMEPLATE, BLANK, FOR VALVES WITH SPRINGS OR DETENTS                  |
| 15  | 2   | V-81      | SCREW, 8-32 X 5/16, SOCKET SET, FULL DOG POINT                        |
| 14  | 4   | V-1       | SCREW, 10-24 X 2, SOCKET HEAD CAP                                     |
| 13  | 1   | V-19      | PLUG, SOCKET PIPE 1/8" NPT (#601-3 PITTSBURG PLUG PART #.)            |
| 12  | 1   | SEC3-1    | END CAP, NON-VENTED, 380 AL, 1/4" & 3/8" VALVES                       |
| 11  | 2   | AY-38T-11 | CLASSIC SOLENOID - STANDARD, COMPLETE OPER, TAPPED EXH., 120/60       |
| 10  | 2   | V-85      | O-RING, BUNA-N, 70 DURO, AS-010, (REF 1/4 X 3/8 X 1/16), CLASSIC OVRD |
| 9   | 2   | OS3W      | SPRING - OVERRIDE RETURN, "CLASSIC" SOLENOID                          |
| 8   | 2   | OP3-W     | OVERRIDE PIN - SPRING RETURN, 1/4" & 3/8" VALVE                       |
| 7   | 1   | PB3-4EW   | ADAPTOR - DBL SOL., NON-LOCKING OVERRIDE, 1/4" & 3/8" VALVE           |
| 6   | 1   | PBG3      | GASKET - PIGGY BACK, DOUBLE SOLENOID, 1/4" & 3/8" VALVE               |
| 5   | 1   | AY-EY3D   | ASSY - SPR CTR, REGEN CTR SPL, CLASSIC SOLENOID, 1/4 & 3/8 VALVES     |
| 4   | 8   | V-38      | SCREW, 10-24 X 3/4, SOCKET HEAD CAP                                   |
| 3   | 2   | ECG3      | GASKET - END CAP, 1/4" & 3/8" VALVE                                   |
| 2   | 6   | V-39      | O-RING, VITON, STD BODY, 1/4" & 3/8" VALVES                           |
| 1   | 1   | B2-6E     | BODY - SOLID, PIGGY BACK, ANODIZED, 1/4" SIDE PORT VALVE              |
| FLG | QTY | PART NO   | DESCRIPTION   |

|   |                |   |  |
|---|----------------|---|--|
| LIMITS ON DIMENSIONS<br>UNLESS<br>OTHERWISE SPECIFIED   |                | 2-PL DECIMAL $\pm .01$<br>3-PL DECIMAL $\pm .005$<br>FRACTIONAL $\pm 1/64$<br>ANGULAR $\pm 1/2^\circ$ | <b>AAA PRODUCTS INTERNATIONAL</b><br>7114 Harry Hines Blvd<br>Dallas, TX 75235 |
| DRAWN: RMckenna   | DATE: 5/3/2020 | CHECKED: KWalte   | DATE: 5/3/2020   |
| SCALE: 1 : 1  | SHEET: 1 OF 1  | RELEASED: HWomack   | DATE: 5/3/2020   |
| TITLE:<br><b>1/4" SIDE PORT, DBL SOL, 3 POS,<br/>REGEN SPR CTR, CLASSIC, 120/60,<br/>NON-LCKNG OVRD, TPD VENT</b> |                | PART NO.:<br><b>SY2DONT</b>   | REV.:  |

THE INFORMATION CONTAINED WITHIN THIS DOCUMENT IS PROPRIETARY TO AAA PRODUCTS AND MAY NOT BE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT