


ALIGN HOLES IN GASKET AS SHOWN.  
(FOR EXTERNAL PILOT PRESSURE, REMOVE PIGGY BACK  
BLOCK AND ROTATE 180°. LEAVE GASKET AS SHOWN. REMOVE  
1/8" PLUG AND CONNECT SUPPLY PRESSURE - 160 PSI MAX.)

NOTES:  
1) ALWAYS GIVE VALVE MODEL AND PART NUMBER WHEN ORDERING PARTS.  
2) FOR DIFFERENT VOLTAGES OTHER THAN 120/60, REPLACE SOLENOID OPERATOR WITH OPERATOR LISTED IN TABLE BELOW.

|                                                                                                              |  |                                                                                  |  |                                                                                                                                                                          |  |                 |  |
|--------------------------------------------------------------------------------------------------------------|--|----------------------------------------------------------------------------------|--|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|-----------------|--|
| LIMITS ON DIMENSIONS<br>UNLESS<br>OTHERWISE SPECIFIED                                                        |  | 2-PL DECIMAL ± .01<br>3-PL DECIMAL ± .005<br>FRACTIONAL ± 1/64<br>ANGULAR ± 1/2° |  |  <b>AAA PRODUCTS<br/>INTERNATIONAL</b><br>7114 Harry Hines Blvd<br>Dallas, TX 75235 |  |                 |  |
| DRAWN: RMckenna                                                                                              |  | DATE: 2/22/2025                                                                  |  | CHECKED: Kwaite                                                                                                                                                          |  | DATE: 2/22/2025 |  |
| SCALE: 1 : 1                                                                                                 |  | SHEET: 1 OF 1                                                                    |  | RELEASED: HWomack                                                                                                                                                        |  | DATE: 2/22/2025 |  |
| LACE OPERATOR                                                                                                |  |                                                                                  |  | PART NO.:                                                                                                                                                                |  | REV.:           |  |
| TITLE:<br>3/8" SIDE PORT, DBL SOL, 3 POS,<br>SPR REGEN CTR, EXPL PROOF, 120/60,<br>PUSH OVRD. THD INDCTR PIN |  |                                                                                  |  | SY3DXOPK                                                                                                                                                                 |  |                 |  |
| AY-38X-5                                                                                                     |  |                                                                                  |  |                                                                                                                                                                          |  |                 |  |
| AY-38X-8                                                                                                     |  |                                                                                  |  |                                                                                                                                                                          |  |                 |  |
| AY-38X-17                                                                                                    |  |                                                                                  |  |                                                                                                                                                                          |  |                 |  |

THE INFORMATION CONTAINED WITHIN THIS DOCUMENT IS PROPRIETARY TO AAI PRODUCTS AND MAY NOT BE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT

