



POSITION GASKET ON END OF VALVE SO GASKET COVERS PILOT HOLE BOTH SIDES (SIDE 'A' SHOWN)

NOTES:
 1) ALWAYS GIVE VALVE MODEL AND PART NUMBER WHEN ORDERING PARTS.
 2) LUBRICATE SPRINGS, AND DETENT BALL.

17	1	SC8-2	CLEVIS - POS. A & C DETENTS, 3/4" & 1" VALVE
16	1	SPK-8	KIT - SUBPLATE MOUNT, 1" SUBPLATE VALVES
15	1	BP8-1	BODY, 1" SUBPLATE, UPPER PILOTS, ANODIZED
14	1	AN-114	NAME PLATE, BLANK, FOR VALVES WITH SPRINGS OR DETENTS.
13	1	V-8	SCREW, 5/16-18 X 5/16, SOCKET SET, CUP POINT
12	1	DS48	SPRING - DETENT, 1/2", 3/4" & 1" VALVE
11	1	V-4	BALL, CHROME STEEL 1/4 DIA. FOR DETENT
10	6	V-30	O-RING, BUNA-N, 70 DURO, AS-220, (REF 1-3/8 X 1-5/8 X 1/8), 3/4" & 1" VALVES
9	2	V-212	SCREW, #2 X 3/16 DRIVE, TYPE U, OVAL HEAD, STAINLESS STEEL
8	8	V-46	SCREW, 1/4-20 X 3/4, SOCKET HEAD CAP
7	1	V-51-SS	PIN, ROLL 1/4 X 1 FOR 3/4 & 1" HAND FOOT & CAM VALVES, STAINLESS STEEL
6	1	V-70	PIN, ROLL 1/4 X 1 1/8 FOR 3/4 & 1" HAND AND FOOT VALVES
5	1	HL8-9	HAND LEVER ASSEMBLY, 3/4" & 1" VALVE
4	1	FE8-3	END CAP, HAND & FOOT, DETENT, STEEL, NICKEL PLT, 3/4" & 1" VALVES
3	1	PEC48-3	END CAP, VENTED, 380 AL, 1/2", 3/4" & 1" VALVES
2	1	S8	SPOOL - STANDARD, 2 POS, CLSD CTR, 3/4" & 1" VALVE
1	2	ECG48	GASKET - END CAP, 1/2", 3/4" & 1" VALVE
FLG	QTY	PART NO	DESCRIPTION

LIMITS ON DIMENSIONS
 UNLESS OTHERWISE SPECIFIED
 2-PL DECIMAL ± .01
 3-PL DECIMAL ± .005
 FRACTIONAL ± 1/64
 ANGULAR ± 1/2°

AAA PRODUCTS INTERNATIONAL
 7114 Harry Hines Blvd
 Dallas, TX 75235

DRAWN: RMckenna DATE: 4/30/2015 CHECKED: KWaite DATE: 5/30/2015
 SCALE: 3/4 SHEET: 1 OF 1 RELEASED: HWomack DATE: 5/30/2015

TITLE: 1" SUBPLATE, LEVER, 2 POS, DETENT, LEVER RTRN	PART NO.: HD8PQ	REV.:
--	---------------------------	-------

THE INFORMATION CONTAINED WITHIN THIS DOCUMENT IS PROPRIETARY TO AAA PRODUCTS AND MAY NOT BE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT

D:\Engineering\product\Valve Assembly\Lever\HD8PQ.dwg