


POSITION GASKET ON END OF VALVE SO MOUNTING HOLES ALIGN, BOTH ENDS (SIDE 'A' SHOWN)

| FLG | QTY | PART NO  | DESCRIPTION  |
|-----|-----|----------|--|
| 15  | 2   | V-212    | SCREW, #2 X 3/16 DRIVE, TYPE U, OVAL HEAD, STAINLESS STEEL                         |
| 14  | 1   | AN-106   | NAMEPLATE, BLANK, STAINLESS STEEL  |
| 13  | 1   | V-501    | NUT - PANEL MOUNT, YELLOW BRASS, 1/4" & 3/8" VALVE                                 |
| 12  | 4   | V-162-SS | SCREW, 10-24 X 5/8, SOCKET HEAD CAP, STAINLESS STEEL                               |
| 11  | 1   | V-543    | KNOB, RED (BRASS 5/16-18 INSERT), PALM, 1 13/16 DIA, PUSH/PULL, 1/4" & 3/8" VALVES |
| 10  | 1   | PBS3     | STUD - PALM, STANDARD, STAINLESS, 1/4" & 3/8" VALVE                                |
| 9   | 1   | PEC3-9   | END CAP, PALM, PANEL MNT, 303 STAINLESS STEEL, 1/4" & 3/8" VALVE                   |
| 8   | 1   | V-43     | WASHER - SPRING CTR, 302/304 STAINLESS STEEL, 1/4" & 3/8" VALVES                   |
| 7   | 1   | SSH3-SS  | SPOOL - STANDARD, 2 POS, CLSD CTR, STAINLESS, 1/4" & 3/8" VALVE                    |
| 6   | 1   | CS3-2    | SPRING - RETURN, (HO & KO) 1/4" & 3/8" VALVES                                      |
| 5   | 1   | SEC3-3   | END CAP, VENTED, STAINLESS STEEL, 1/4" & 3/8" VALVES                               |
| 4   | 4   | V-500    | SCREW, 10-24 X 3/4, SOCKET HEAD CAP, STAINLESS                                     |
| 3   | 2   | ECG3     | GASKET - END CAP, 1/4" & 3/8" VALVE  |
| 2   | 6   | V-39     | O-RING, VITON, STD BODY, 1/4" & 3/8" VALVES  |
| 1   | 1   | B3-2-SS  | BODY - STAINLESS STEEL, PLAIN, NO PILOTS, 3/8" SIDE PORT VALVE                     |

**SECTION A-A**  
SCALE 1 : 1  
VIEW FROM 3 PORT SIDE

- NOTES:
- 1) ALWAYS GIVE VALVE MODEL AND PART NUMBER WHEN ORDERING PARTS.
  - 2) LUBRICATE DETENT BALL, SPRING AND STUD.
  - 3) APPLY ANTI-SEIZE COMPOUND LIGHTLY TO THE FIRST 1/4" OF THE SCREW THREAD. APPLICATION SHOULD BE AROUND THE THREAD OF THE SCREW.
  - 4) DO NOT LOCTITE PALM KNOB TO STUD.
  - 5) NOT ALL PARTS ARE 316 STAINLESS, SOME ARE 18-8, 303 STAINLESS AND BRASS.



|   |                 |  |  |
|---|-----------------|--|--|
| LIMITS ON DIMENSIONS UNLESS OTHERWISE SPECIFIED   |                 | 2-PL DECIMAL ± .01<br>3-PL DECIMAL ± .005<br>FRACTIONAL ± 1/64<br>ANGULAR ± 1/2° | <b>AAA PRODUCTS INTERNATIONAL</b><br>7114 Harry Hines Blvd<br>Dallas, TX 75235 |
| DRAWN: RMcKenna   | DATE: 5/10/2015 | CHECKED: KWaite  |  |
| SCALE: 1 : 1  | SHEET: 1 OF 1   | RELEASED: HWomack  | DATE: 5/17/2015  |
| TITLE:<br><b>3/8" SIDE PORT, PALM, 2 POS, SPRING RTNR, PANEL MNT, RED KNOB, STAINLESS</b> |                 | PART NO.:<br><b>KO3JRSS</b>  | REV.:<br><b>B</b>  |

| NO. | DATE      | REVISION                                   |
|-----|-----------|--|
| B   | 8/19/2020 | REPLACED S3-SS WITH SSH3-SS, ADDED V-43.   |
| A   | 7/20/2016 | CHANGED SPRING FROM CS3-5 TO WEAKER CS3-2. |

THE INFORMATION CONTAINED WITHIN THIS DOCUMENT IS PROPRIETARY TO AAA PRODUCTS AND MAY NOT BE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT