



POSITION GASKET ON END OF VALVE SO MOUNTING HOLES ALIGN, BOTH ENDS (SIDE 'A' SHOWN)

- NOTES:
- 1) ALWAYS GIVE VALVE MODEL AND PART NUMBER WHEN ORDERING PARTS.
  - 2) LUBRICATE DETENT BALL, SPRING AND STUD.
  - 3) APPLY ANTI-SEIZE COMPOUND LIGHTLY TO THE FIRST 1/4" OF THE SCREW THREAD. APPLICATION SHOULD BE AROUND THE THREAD OF THE SCREW.
  - 4) DO NOT LOCTITE PALM KNOB TO STUD.
  - 5) NOT ALL PARTS ARE 316 STAINLESS, SOME ARE 18-8, 303 STAINLESS AND BRASS.

| FLG | QTY | PART NO   | DESCRIPTION  |
|-----|-----|-----------|--|
| 18  | 2   | V-212     | SCREW, #2 X 3/16 DRIVE, TYPE U, OVAL HEAD, STAINLESS STEEL                         |
| 17  | 1   | AN-106    | NAMEPLATE, BLANK, STAINLESS STEEL  |
| 16  | 2   | V-14-SS   | BALL, 440C STAINLESS STEEL, 3/16 DIA. FOR DETENT                                   |
| 15  | 2   | DS3-1     | SPRING, DETENT, STAINLESS, 1/4" & 3/8" VALVE. LEE SPRING # LC 029B 0 S.            |
| 14  | 2   | V-21-SS   | SCREW, 1/4-20 X 3/16, SOCKET SET, CUP POINT, 18-8 SS                               |
| 13  | 4   | V-162-SS  | SCREW, 10-24 X 5/8, SOCKET HEAD CAP, STAINLESS STEEL                               |
| 12  | 1   | V-501     | NUT - PANEL MOUNT, YELLOW BRASS, 1/4" & 3/8" VALVE                                 |
| 11  | 1   | V-543     | KNOB, RED (BRASS 5/16-18 INSERT), PALM, 1 13/16 DIA, PUSH/PULL, 1/4" & 3/8" VALVES |
| 10  | 1   | PBS3-189  | STUD - PALM, 189 ACTION, STAINLESS 1/4" & 3/8" VALVES                              |
| 9   | 1   | PEC3-12DD | END CAP, PALM, PANEL MNT, DBL DETENT, 303 STAINLESS STEEL, 1/4" & 3/8" VALVE       |
| 8   | 1   | SSH3-SS   | SPOOL - STANDARD, 2 POS, CLSD CTR, STAINLESS, 1/4" & 3/8" VALVE                    |
| 7   | 3   | V-43      | WASHER - SPRING CTR, 302/304 STAINLESS STEEL, 1/4" & 3/8" VALVES                   |
| 6   | 1   | CS3-1     | SPRING - CENTERING, 1/4" & 3/8" VALVES   |
| 5   | 1   | SEC3-3    | END CAP, VENTED, STAINLESS STEEL, 1/4" & 3/8" VALVES                               |
| 4   | 4   | V-38-SS   | SCREW, 10-24 X 3/4, SOCKET HEAD CAP, 18-8 SS                                       |
| 3   | 2   | ECG3      | GASKET - END CAP, 1/4" & 3/8" VALVE  |
| 2   | 6   | V-39      | O-RING, VITON, STD BODY, 1/4" & 3/8" VALVES  |
| 1   | 1   | B3-2-SS   | BODY - STAINLESS STEEL, PLAIN, NO PILOTS, 3/8" SIDE PORT VALVE                     |
| FLG | QTY | PART NO   | DESCRIPTION  |

SECTION A-A  
SCALE 1 : 1  
VIEW FROM 3 PORT SIDE

|   |                 |  |                      |  |
|---|-----------------|--|----------------------|--|
| LIMITS ON DIMENSIONS<br>UNLESS OTHERWISE SPECIFIED  |                 | 2-PL DECIMAL ± .01<br>3-PL DECIMAL ± .005<br>FRACTIONAL ± 1/64<br>ANGULAR ± 1/2° |                      | <b>AAA PRODUCTS INTERNATIONAL</b><br>7114 Harry Hines Blvd<br>Dallas, TX 75235 |
| DRAWN: RMckenna   | DATE: 9/14/2016 | CHECKED: KWaite  | DATE: 9/14/2016      |  |
| SCALE: 1 : 1  | SHEET: 1 OF 1   | RELEASED: HWomack  | DATE: 9/14/2016      |  |
| TITLE:<br>3/8" SIDE PORT, PALM, 3 POS,<br>DETENT C, SPR CTR FRM A, REGEN CTR,<br>RED KNOB, PANEL MNT, STAINLESS |                 |  | PART NO.:<br>KW3JRSS | REV.:<br>A   |

| A | NO.       | DATE                         | REVISION |
|---|-----------|------------------------------|----------|
|   | 8/19/2020 | REPLACED S3-SS WITH SSH3-SS. |          |

THE INFORMATION CONTAINED WITHIN THIS DOCUMENT IS PROPRIETARY TO AAA PRODUCTS AND MAY NOT BE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT