



NOTES:
 1) ALWAYS GIVE VALVE MODEL AND PART NUMBER WHEN ORDERING PARTS.
 2) ALIGN ENDCAP PILOT HOLE WITH BODY PILOT HOLE, BOTH ENDS.
 3) INSERT PLUG IN ENDCAPS, BOTH ENDS.

16	1	SPK-16	KIT - SUBPLATE MOUNT, 2" SUBPLATE VALVES
15	2	V-212	SCREW, #2 X 3/16 DRIVE, TYPE U, OVAL HEAD, STAINLESS STEEL
14	1	AN-115	NAMEPLATE, BLANK, FOR HE,KE,KD,RR,D,CR,PP,SR,SS VALVES
13	4	V-162	SCREW, 10-24 X 5/8, SOCKET HEAD CAP
12	2	V-92	O-RING, BUNA-N, 70 DURO, AS-014, (REF 1/2 X 5/8 X 1/16), 3/8" SUBPLATE
11	1	V-522	PLATE - COVER, 1-1/2" & 2" VALVE
10	2	V-89	O-RING, BUNA-N, 70 DURO, AS-110, (REF 3/8 X 9/16 X 3/32), 1" & 2" SUBPLATE PILOT
9	3	V-231	PLUG, SOCKET PRESSURE 1/16-27X 7/8 TAPER FOR 122V,192V, FOR EC
8	2	V-129	U-CUP, 1-5/8 X 1-1/8 X 1/4, NITRILE
7	12	V-143	SCREW, 5/16-18 X 2, SOCKET HEAD CAP
6	2	PCE12E	ENDCAP - PRESSURE CTR, SOLID, 6061-T6 AL, 1-1/2" & 2" VALVES
5	2	V-128	O-RING, BUNA-N, 70 DURO, AS-229, (REF 2-3/8 X 2-5/8 X 1/8), 3 POS, 1-1/2" & 2" VALVES
4	2	SPC12	SPOOL - PRESS. CTR, 1 1/2" & 2" VALVE
3	1	S12G	SPOOL - 'G', FLOAT CTR, 1 1/2" & 2" VALVE
2	6	V-123	O-RING, BUNA-N, 70 DURO, AS-331, (REF 2-1/4 X 2-5/8 X 3/16), 1-1/2" & 2" VALVES
1	1	BP16-8	BODY, 2" SUBPLATE, PIGGY BACK & LOWER PILOTS
FLG	QTY	PART NO	DESCRIPTION

LIMITS ON DIMENSIONS UNLESS OTHERWISE SPECIFIED		2-PL DECIMAL ± .01 3-PL DECIMAL ± .005 FRACTIONAL ± 1/64 ANGULAR ± 1/2°		AAA PRODUCTS INTERNATIONAL 7114 Harry Hines Blvd Dallas, TX 75235
DRAWN: RMckenna	DATE: 9/23/2014	CHECKED: KWaite	DATE: 3/26/2015	
SCALE: 1/2	SHEET: 1 OF 1	RELEASED: HWormack	DATE: 3/26/2015	
TITLE: 2" SUBPLATE, DBL PILOT, 3 POS, PRESS CTR, PILOT SHFT, FLOAT CTR SPL			PART NO.: GY16PG	REV.:

THE INFORMATION CONTAINED WITHIN THIS DOCUMENT IS PROPRIETARY TO AAA PRODUCTS AND MAY NOT BE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT

D:\Engineering\product\Valve Assembly\Photo\VALVE GY16PG.TIF