



| FLG | QTY | PART NO | DESCRIPTION |
|-----|-----|----------|--|
| 15 | 1 | SPK-4 | KIT - 1/2" SUBPLATE MOUNTING WITH SCREWS |
| 14 | 2 | V-212 | SCREW, #2 X 3/16 DRIVE, TYPE U, OVAL HEAD, 316 STAINLESS STEEL |
| 13 | 1 | AN-114 | NAME PLATE, BLANK, FOR VALVES WITH SPRINGS OR DETENTS. |
| 12 | 8 | V-46 | SCREW, 1/4-20 X 3/4 SHCS, HOLDS E.C TO 1/2-1" VALVES |
| 11 | 2 | EMG3 | GASKET - END MOUNT SOLENOID, BUNA-N, 1/4" & 3/8" VALVES |
| 10 | 1 | SSA48-1E | ADAPTOR, END MNT SOLENOID, 1/2", 3/4" & 1" VALVE |
| 9 | 2 | V-550-1 | NASS SYSTEM 8 SOLENOID BODY(1417 16.6-00) ULTRAMIN B3EG10. |
| 8 | 2 | SEC3-7 | PLATE, RE-INFORCEMENT, SOLENOID, STAMPED, 304 STAINLESS |
| 7 | 8 | V-584 | SCREW, 10-24 X 1 BUTTON HEAD SOCKET CAP WITH MICROSPHERE APPLIED TO THREADS. |
| 6 | 2 | V-654-3 | COIL - 30MM WIDE, ISO 4400 DIN, 24VDC |
| 5 | 2 | V-556 | NUT, SOLENOID, TOP EXHAUST, KNURLED |
| 4 | 1 | AY-ESY4 | SPRING CENTER SPOOL ASSY, END MOUNT SOLENOID, 1/2" VALVES |
| 3 | 2 | ECG48 | GASKET - END CAP, 1/2", 3/4" & 1" VALVE |
| 2 | 6 | V-6 | O-RING, 1 1/8 X 1 3/8 X 1/8 CS 70 D.FOR 1/2 VALVE & 1"SP(V-90) BUNA-N |
| 1 | 1 | BP4-1 | VALVE BODY 1/2" - W/UPPER PILOT, BOTTOM PORTED |

| | | | | |
|---|------------------|--|-------------------|--|
| LIMITS ON DIMENSIONS UNLESS OTHERWISE SPECIFIED | | 2-PL DECIMAL ± .01 3-PL DECIMAL ± .005 FRACTIONAL ± 1/64 ANGULAR ± 1/2° | | AAA PRODUCTS INTERNATIONAL 7114 Harry Hines Blvd Dallas, TX 75235 |
| DRAWN: RMckenna | DATE: 11/21/2014 | CHECKED: KWaite | DATE: 11/21/2014 | |
| SCALE: 1:1 | SHEET: 1 OF 1 | RELEASED: HWomack | DATE: 11/21/2014 | |
| TITLE: 1/2" SUBPLATE, DBL SOL, 3 POS, SPR CTR, SOL SHFT, CLSD CTR SPL, EXT PILOT, ISO4400 DIN, 24VDC | | | PART NO.: 755V | REV.: |

THE INFORMATION CONTAINED WITHIN THIS DOCUMENT IS PROPRIETARY TO AAA PRODUCTS AND MAY NOT BE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT

P:\Engineering\Inventory Files\Internal Drawings\Valves Assembly\Standard\Special\755V.dwg