



NOTES:
 1) ALWAYS GIVE VALVE MODEL AND PART NUMBER WHEN ORDERING PARTS.
 2) SEE DRAWING AY-38X FOR SOLENOID ASSEMBLY AND AY-SAH3LOC FOR SPOOL ASSEMBLY.

17	2	V-212	SCREW, #2 X 3/16 DRIVE, TYPE U, OVAL HEAD, 316 STAINLESS STEEL
16	1	AN-114	NAME PLATE, BLANK, FOR VALVES WITH SPRINGS OR DETENTS.
15	4	V-38-SS	SCREW, 10-24 X 3/4 SHCS, 18-8 SS
14	1	AY-SAH3LOC-SA	ASSY - SPR RTRN TO POS A, CLASSIC SOL W/LEVER, LOCKOUT C, SS & EN W/AL SPL, 1/4" & 3/8"
13	1	AY-38X-8	CLASSIC SOLENOID - EXPLOSION PROOF, 24VDC, 88/60
12	1	V-19-SS	PLUG, SOCKET PIPE 1/8"-27 NPT, 7/8 TAPER, PLAIN, FLUSH SEAL, STAINLESS STEEL
11	4	V-1-SS	SCREW, 10-24 X 2 SHCS FOR SOL. ADAPTOR TO BODY, STAINLESS STEEL
10	1	PB3-1E-TC	ADAPTOR - SINGLE SOLENOID, TUFRAM, 1/4" & 3/8" VALVES
9	1	PBG3-1	GASKET - PIGGY BACK, SINGLE SOLENOID, 1/4" & 3/8" VALVE
8	1	HE3-SLO	END CAP, LEVER, 303 STAINLESS, LOCKOUT, 1/4" & 3/8" VALVES
7	1	HL3-SS	HAND LEVER, 303 STAINLESS STEEL, 1/4" & 3/8" VALVE
6	1	V-580	KNOB, BLACK (BRASS 3/8-16 INSERT), 1" DIA BALL
5	1	V-508-SS	PIN, ROLL 3/16 X 5/8", 18-8 SS
4	4	V-162-SS	SCREW, 10-24 X 5/8 STAINLESS STEEL
3	2	ECG3	GASKET - END CAP, 1/4" & 3/8" VALVE
2	6	V-39	O-RING, STD BODY, VITON, 1/4" & 3/8" VALVES
1	1	B3-6E-TC	BODY - SOLID, PIGGY BACK, TUFRAM, 3/8" SIDE PORT VALVE
FLG	QTY	PART NO	DESCRIPTION

LIMITS ON DIMENSIONS UNLESS OTHERWISE SPECIFIED		2-PL DECIMAL ± .01 3-PL DECIMAL ± .005 FRACTIONAL ± 1/64 ANGULAR ± 1/2°		AAA PRODUCTS INTERNATIONAL 7114 Harry Hines Blvd Dallas, TX 75235
DRAWN: RMckenna	DATE: 9/11/2017	CHECKED: KWaite	DATE: 9/11/2017	
SCALE: 1 : 1	SHEET: 1 OF 1	RELEASED: HWomack	DATE: 9/11/2017	
TITLE: 3/8" SIDE PORT, SNGL SOL, 2 POS, SPR RTRN, SOL SHFT, LEVER ASSIST, EXPL PRF, 24VDC, LO POS A, TUFRAM			PART NO.: 802V	REV.:

THE INFORMATION CONTAINED WITHIN THIS DOCUMENT IS PROPRIETARY TO AAA PRODUCTS AND MAY NOT BE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT

P:\Engineering\Inventory Files\Internal Drawings\Valves Assembly\Classic\Special\802V.dwg