

ALIGN PILOT AND HOLE IN GASKET SIDES 'B' ONLY FOR EXTERNAL PILOT OPERATION - ROTATE THE ROUND ALUMINUM ADAPTOR 180 DEGREES. REMOVE 1/8" NPTF PLUG AND SUPPLY 50-150 PSI TO 1/8" NPTF PILOT PORT IN ADAPTOR.


POSITION GASKET ON END OF VALVE SO GASKET COVERS PILOT HOLE SIDE 'A' ONLY

NOTES:  
1) ALWAYS GIVE VALVE MODEL AND PART NUMBER WHEN ORDERING PARTS.

|     |     |          |  |
|-----|-----|----------|--|
| 18  | 1   | SPK-4    | KIT - SUBPLATE MOUNT, 1/2" SUBPLATE VALVES   |
| 17  | 2   | V-212    | SCREW, #2 X 3/16 DRIVE, TYPE U, OVAL HEAD, STAINLESS STEEL                           |
| 16  | 1   | AN-114   | NAMEPLATE, BLANK, FOR VALVES WITH SPRINGS OR DETENTS                                 |
| 15  | 1   | V-19     | PLUG, SOCKET PIPE 1/8" NPT, 7/8 TAPER, FLUSH SEAL                                    |
| 14  | 1   | V-10     | PIN, ROLL 3/16 X 7/8, STEEL  |
| 13  | 1   | HL4-9    | HAND LEVER ASSEMBLY, 1/2" VALVE  |
| 12  | 1   | FE4-1    | END CAP - HAND & FOOT, 380 AL, 1/2" VALVE  |
| 11  | 1   | AY-ESAH4 | ASSY - NO DETENT, RTRN TO POS A, END MNT SOL W/LEVER ASSIST, 1/2" VALVES             |
| 10  | 1   | V-599-1  | SOL OPER, END MOUNT, LOCKING O'RIDE  |
| 9   | 1   | SEC3-7   | PLATE, RE-INFORCEMENT, SOLENOID, STAMPED, 304 STAINLESS                              |
| 8   | 4   | V-584    | SCREW, 10-24 X 1, BUTTON HEAD SOCKET CAP WITH MICROSPHERE APPLIED TO THREADS.        |
| 7   | 1   | V-569-1  | SYSTEM 8 COIL 120 50/60.NASS # 0561 38.1 00/4984.                                    |
| 6   | 1   | V-567W   | E SERIES SINTERED BRONZE MUFFLER, DUST EXCLUDER, V-613 LOCK WASHER                   |
| 5   | 1   | EMG3     | GASKET - END MOUNT SOLENOID, BUNA-N, 1/4" & 3/8" VALVES                              |
| 4   | 8   | V-46     | SCREW, 1/4-20 X 3/4, SOCKET HEAD CAP   |
| 3   | 2   | ECG48    | GASKET - END CAP, 1/2", 3/4" & 1" VALVE  |
| 2   | 6   | V-6      | O-RING, BUNA-N, 70 DURO, AS-216, (REF 1-1/8 X 1-3/8 X 1/8), 1/2" VALVES, 1" SUBPLATE |
| 1   | 1   | BP4-1    | BODY, 1/2" SUBPLATE, UPPER PILOTS, ANODIZED  |
| FLG | QTY | PART NO  | DESCRIPTION  |

|   |  |  |  |  |                 |                 |
|---|--|--|--|--|-----------------|-----------------|
| LIMITS ON DIMENSIONS UNLESS OTHERWISE SPECIFIED   |  | 2-PL DECIMAL ± .01<br>3-PL DECIMAL ± .005<br>FRACTIONAL ± 1/64<br>ANGULAR ± 1/2° |  | <b>AAA PRODUCTS INTERNATIONAL</b><br>7114 Harry Hines Blvd<br>Dallas, TX 75235 |                 |                 |
| DRAWN: RMcKenna   |  | DATE: 4/19/2021  |  |  | CHECKED: KWaite | DATE: 4/19/2021 |
| SCALE: 3/4  |  | SHEET: 1 OF 1  |  | RELEASED: HWomack  |                 | DATE: 4/19/2021 |
| TITLE:<br><b>1/2" SUBPLATE, SNGL SOL, 2 POS, SPR RTRN, FLYING LEAD, 120/60, LEVER ASST, EXCLDR, SIDE VENT</b> |  |  |  | PART NO.:  |                 | REV.:           |
|   |  |  |  | <b>ESAH4PMOL</b>   |                 |                 |

| COIL VOLTAGES    |              |
|------------------|--------------|
| PART NO          | REPLACE COIL |
| ESAH4PMOL 12VDC  | V-569-2      |
| ESAH4PMOL 24VDC  | V-569-3      |
| ESAH4PMOL 240/60 | V-569-4      |



SECTION A-A  
SCALE 3/4

THE INFORMATION CONTAINED WITHIN THIS DOCUMENT IS PROPRIETARY TO AAA PRODUCTS AND MAY NOT BE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT

D:\Engineering\product\Valves\AssemblyStandards\SA1\DWG\ESAH4PMOL.dwg