

ALIGN PILOT AND HOLE IN GASKET, SIDE 'B' ONLY FOR EXTERNAL PILOT OPERATION - ROTATE THE ROUND ALUMINUM ADAPTOR 180 DEGREES. REMOVE 1/8" NPTF PLUG AND SUPPLY 50-150 PSI TO 1/8" NPTF PILOT PORT IN ADAPTOR.

POSITION GASKET ON END OF VALVE SO GASKET COVERS PILOT HOLE SIDE 'A' ONLY

NOTES:  
1) ALWAYS GIVE VALVE MODEL AND PART NUMBER WHEN ORDERING PARTS.


|     |     |          |   |
|-----|-----|----------|---|
| 18  | 1   | SPK-8    | KIT - SUBPLATE MOUNT, 1" SUBPLATE VALVES                                      |
| 17  | 2   | V-212    | SCREW, #2 X 3/16 DRIVE, TYPE U, OVAL HEAD, STAINLESS STEEL                    |
| 16  | 1   | AN-114   | NAMEPLATE, BLANK, FOR VALVES WITH SPRINGS OR DETENTS                          |
| 15  | 1   | V-19     | PLUG, SOCKET PIPE 1/8" NPT, 7/8 TAPER, FLUSH SEAL                             |
| 14  | 1   | V-70     | PIN, ROLL 1/4 X 1 1/8 FOR 3/4 & 1" HAND AND FOOT VALVES                       |
| 13  | 1   | HL8-9    | HAND LEVER ASSEMBLY, 3/4" & 1" VALVE  |
| 12  | 1   | FEB      | END CAP, HAND & FOOT, STEEL, NICKEL PLATE, 3/4" & 1" VALVES                   |
| 11  | 1   | AY-ESAH8 | ASSY - NO DETENT, RTRN TO POS A, END MNT SOL W/LEVER ASSIST, 3/4" & 1" VALVES |
| 10  | 1   | V-599-1  | SOL OPER, END MOUNT, LOCKING O'RIDE   |
| 9   | 1   | SEC3-7   | PLATE, RE-INFORCEMENT, SOLENOID, STAMPED, 304 STAINLESS                       |
| 8   | 4   | V-584    | SCREW, 10-24 X 1, BUTTON HEAD SOCKET CAP WITH MICROSPHERE APPLIED TO THREADS. |
| 7   | 1   | V-600-1  | COIL - 1/2 NPTF HUB 120V 50/60HZ, NASS P/N 0561 44.1-00/4984                  |
| 6   | 1   | V-562    | NUT, SOLENOID, SIDE EXHAUST   |
| 5   | 1   | EMG3     | GASKET - END MOUNT SOLENOID, BUNA-N, 1/4" & 3/8" VALVES                       |
| 4   | 8   | V-46     | SCREW, 1/4-20 X 3/4, SOCKET HEAD CAP  |
| 3   | 2   | ECG48    | GASKET - END CAP, 1/2", 3/4" & 1" VALVE                                       |
| 2   | 6   | V-30     | O-RING, BUNA-N, 70 DURO, AS-220, (REF 1-3/8 X 1-5/8 X 1/8), 3/4" & 1" VALVES  |
| 1   | 1   | BP8-1    | BODY, 1" SUBPLATE, UPPER PILOTS, ANODIZED                                     |
| FLG | QTY | PART NO  | DESCRIPTION   |

LIMITS ON DIMENSIONS  
UNLESS OTHERWISE SPECIFIED  
2-PL DECIMAL ± .01  
3-PL DECIMAL ± .005  
FRACTIONAL ± 1/64  
ANGULAR ± 1/2°

**AAA PRODUCTS INTERNATIONAL**  
7114 Harry Hines Blvd  
Dallas, TX 75235

|   |                 |                               |                 |
|---|-----------------|-------------------------------|-----------------|
| DRAWN: RMckenna   | DATE: 4/18/2021 | CHECKED: KWaite               | DATE: 4/18/2021 |
| SCALE: 5/8  | SHEET: 1 OF 1   | RELEASED: HWomack             | DATE: 4/18/2021 |
| TITLE:<br><b>1" SUBPLATE, SNGL SOL, 2 POS,<br/>SPR RTRN, MOLD-OVER, 120/60,<br/>LEVER ASST, LCKNG OVRD, SIDE VENT</b> |                 | PART NO.:<br><b>ESAH8PJOC</b> | REV.:           |

| COIL VOLTAGES    |              |
|------------------|--------------|
| PART NO          | REPLACE COIL |
| ESAH8PJOC 12VDC  | V-600-2      |
| ESAH8PJOC 24VDC  | V-600-3      |
| ESAH8PJOC 240/60 | V-600-4      |



THE INFORMATION CONTAINED WITHIN THIS DOCUMENT IS PROPRIETARY TO AAA PRODUCTS AND MAY NOT BE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT