



10 SEE NOTES 2 & 3

- NOTES:  
 1) ALWAYS GIVE VALVE MODEL AND PART NUMBER WHEN ORDERING.  
 2) OPEN MUFFLER 2 TURNS FROM CLOSED POSITION. TIGHTEN LOCK NUT ON MUFFLER.  
 3) INSTALL MUFFLER WITH MAGNALUBE-G GREASE 1 TO 1-1/2 TURNS FROM HAND TIGHT INTO BODY.  
 4) FOR DIFFERENT VOLTAGES OTHER THAN 120/60, REPLACE TOP CONTROL VALVE WITH VALVE LISTED IN TABLE BELOW.

THE FOLLOWING PARTS ARE INCLUDED WITH THE SUBPLATE VALVE AND ARE USED TO ASSEMBLE.

| QTY | PART NO | DESCRIPTION  |
|-----|---------|--|
| 5   | V-92    | O-RING, BUNA-N, 70 DURO, AS-014, (REF 1/2 X 5/8 X 1/16), 3/8" SUBPLATE |
| 4   | V-35    | SCREW, 10-24 X 7/8, SOCKET HEAD CAP                                    |

|     |     |         |   |
|-----|-----|---------|---|
| 12  | 1   | SPK-16  | KIT - SUBPLATE MOUNT, 2" SUBPLATE VALVES  |
| 11  | 1   | ESO3POL | 3/8" SUBPLATE, SNGL SOL, 2 POS, SPR RTRN, 120/60, LCKNG OVRD, DUST EXCLDR             |
| 10  | 2   | MFC2    | ASSEMBLY - MUFFLER FLOW CONTROL, 1/4" NPT   |
| 9   | 3   | V-337   | PLUG, SOCKET 1/4-18 FLUSH SEAL PLUG   |
| 8   | 2   | V-124   | O-RING, BUNA-N, 70 DURO, AS-231, (REF 2-5/8 X 2-7/8 X 1/8), 2 POS, 1-1/2" & 2" VALVES |
| 7   | 2   | V-89    | O-RING, BUNA-N, 70 DURO, AS-110, (REF 3/8 X 9/16 X 3/32), 1" & 2" SUBPLATE PILOT      |
| 6   | 2   | V-231   | PLUG, SOCKET PRESSURE 1/16-27X 7/8 TAPER FOR 122V,192V,FOR EC                         |
| 5   | 12  | V-143   | SCREW, 5/16-18 X 2, SOCKET HEAD CAP   |
| 4   | 2   | PEC12E  | ENDCAP - PILOT, SOLID, 6061-T6 AL, 1-1/2" & 2" VALVES                                 |
| 3   | 1   | S12     | SPOOL - STANDARD, 2 POS - 3 POS CLOSED CTR, 1 1/2" & 2" VALVE                         |
| 2   | 6   | V-123   | O-RING, BUNA-N, 70 DURO, AS-331, (REF 2-1/4 X 2-5/8 X 3/16), 1-1/2" & 2" VALVES       |
| 1   | 1   | BP16-6  | BODY, 2" SUBPLATE, PIGGY BACK   |
| FLG | QTY | PART NO | DESCRIPTION   |

SECTION A-A  
 SCALE 1/2  
 VIEW FROM 3 PORT SIDE

CONTROL VALVE VOLTAGES

| PART NO         | REPLACE WITH   |
|-----------------|----------------|
| ESO16POL 240/60 | ESO3POL 240/60 |
| ESO16POL 24VDC  | ESO3POL 24VDC  |
| ESO16POL 12VDC  | ESO3POL 12VDC  |

LIMITS ON DIMENSIONS  
 UNLESS OTHERWISE SPECIFIED  
 2-PL DECIMAL ± .01  
 3-PL DECIMAL ± .005  
 FRACTIONAL ± 1/64  
 ANGULAR ± 1/2°

DRAWN: RMckenna DATE: 1/10/2016  
 SCALE: 1/2 SHEET: 1 OF 1

TITLE:  
**2" SUBPLATE, SNGL SOL, 2 POS,  
 SPR RTRN, 120/60, LCKNG OVRD,  
 DUST EXCLDR**

**AAA PRODUCTS INTERNATIONAL**  
 PRODUCTS INTERNATIONAL  
 7114 Harry Hines Blvd  
 Dallas, TX 75235

CHECKED: KWaite DATE: 1/10/2016  
 RELEASED: HWomack DATE: 1/10/2016

PART NO.: **ESO16POL** REV.:

THE INFORMATION CONTAINED WITHIN THIS DOCUMENT IS PROPRIETARY TO AAA PRODUCTS AND MAY NOT BE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT