


|     |     |          |  |
|-----|-----|----------|--|
| 16  | 1   | V-607    | O-RING, VITON, 75 DURO, 14MM X 1MM, IP67 NUT SEAL                            |
| 15  | 2   | V-606    | O-RING, VITON, 75 DURO, 8MM X 1MM, IP67 STEM SEAL                            |
| 14  | 1   | EMG3     | GASKET - END MOUNT SOLENOID, BUNA-N, 1/4" & 3/8" VALVES                      |
| 13  | 1   | V-19-SS  | PLUG, SOCKET PIPE 1/8"-27 NPT, 7/8 TAPER, PLAIN, FLUSH SEAL, STAINLESS STEEL |
| 12  | 1   | V-556    | NUT, SOLENOID, TOP EXHAUST, KNURLED  |
| 11  | 1   | V-612-3  | ATEX COIL 24 VDC WITH 3 METER CORD. NASS # 1215 30.1-001/6896.               |
| 10  | 4   | V-584-SS | SCREW, 10-24 X 1, BUTTON HEAD SOCKET CAP, 18-8 OR 303 SS                     |
| 9   | 1   | SEC3-7   | PLATE, RE-INFORCEMENT, SOLENOID, STAMPED, 304 STAINLESS                      |
| 8   | 1   | V-599-1  | SOL OPER, END MOUNT, LOCKING O'RIDE  |
| 7   | 1   | S3       | SPOOL - STANDARD, 2 POS, CLSD CTR, 1/4" & 3/8" VALVE                         |
| 6   | 1   | CS3      | SPRING - RETURN, (EXCEPT HO, KO & PO) 1/4" & 3/8" VALVES                     |
| 5   | 1   | SEC3-3   | END CAP, VENTED, STAINLESS STEEL, 1/4" & 3/8" VALVES                         |
| 4   | 4   | V-38-SS  | SCREW, 10-24 X 3/4, SOCKET HEAD CAP, 18-8 SS                                 |
| 3   | 1   | ECG3     | GASKET - END CAP, 1/4" & 3/8" VALVE  |
| 2   | 6   | V-39     | O-RING, VITON, STD BODY, 1/4" & 3/8" VALVES                                  |
| 1   | 1   | ZB2-1    | BODY - BRASS, UPPER PILOTS (BUTTON BLEEDER), 1/4" SIDE PORT VALVE            |
| FLG | QTY | PART NO  | DESCRIPTION  |

NOTES:  
1) ALWAYS GIVE VALVE MODEL AND PART NUMBER WHEN ORDERING PARTS.  
2) FOR DIFFERENT VOLTAGES OTHER THAN 24VDC, CONSULT FACTORY.



|  |                 |  |                            |  |
|--|-----------------|--|----------------------------|--|
| LIMITS ON DIMENSIONS<br>UNLESS OTHERWISE SPECIFIED   |                 | 2-PL DECIMAL ± .01<br>3-PL DECIMAL ± .005<br>FRACTIONAL ± 1/64<br>ANGULAR ± 1/2° |                            | <b>AAA PRODUCTS INTERNATIONAL</b><br>7114 Harry Hines Blvd<br>Dallas, TX 75235 |
| DRAWN: RMckenna  | DATE: 12/6/2015 | CHECKED: KWaite  | DATE: 12/6/2015            |  |
| SCALE: 1 : 1   | SHEET: 1 OF 1   | RELEASED: HWomack  | DATE: 12/6/2015            |  |
| TITLE:<br>1/4" SIDE PORT, SNGL SOL, 2 POS,<br>SPRING RTRN, BRASS & STAINLESS,<br>ATEX, 24VDC, LCKNG OVRD |                 |  | PART NO.:<br>ZES02TO 24VDC | REV.:  |

THE INFORMATION CONTAINED WITHIN THIS DOCUMENT IS PROPRIETARY TO AAA PRODUCTS AND MAY NOT BE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT