

1/2"-14 NPT CONDUIT CONNECTION  
18" LEADS, 3 WIRE

23/32      6 13/16      3 1/8

1 21/32      1/8" NPTF PILOT PORT

Ø11/32  
4-PLACES

5/16

2 3/16

4 3/8

3.750

5/16

5      1      3

1 21/32

PORTS  
5-PLACES

1.875      1.875

.938      .938

SEE NOTE 1

1.234

1.672

.828

NOT USED

2.953

2.953


3.094

NOTES:

1) REMOTE PILOT CAN BE ROUTED THROUGH SUBPLATE CONNECTION.

1/8" NPTF EXTERNAL PILOT PORT

3 25/64



**AAA**  
PRODUCTS  
INTERNATIONAL

**AAA PRODUCTS  
INTERNATIONAL**  
7114 Harry Hines Blvd  
Dallas, TX 75235

TITLE: 1" SUBPLATE, SNGL SOL, 2 POS,  
PILOT RTRN, EXPL PROOF,  
DUST EXCLDR, EXT PILOT

DRAWING NO.:  
DIM\_ESR8PXLZ

THE INFORMATION CONTAINED WITHIN THIS DOCUMENT IS PROPRIETARY TO AAA PRODUCTS AND MAY NOT BE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT