

4

3

2

1

A

O-RING SIDE

20

19

18

5

SIDE 'B'

4

3

2

1

SECTION A-A
SCALE 1 : 1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

2

1

2

1

2

1

2

1

2

1

2

1

2

1

2

1


2

1


2

1


2



POSITION GASKET ON END OF VALVE
TO SEAL PILOT HOLE
SIDE 'B' ONLY



ALIGN PILOT AND SLOT IN ADAPTOR
WITH GASKET IN BETWEEN SIDE 'A' ONLY
FOR EXTERNAL PILOT OPERATION - ROTATE ADAPTOR
180 DEGREES. REMOVE 1/8" NPTF PLUG AND
SUPPLY 50-150 PSI TO 1/8" NPTF PILOT PORT IN ADAPTOR.



NOTES:

- 1) ALWAYS GIVE VALVE MODEL AND PART NUMBER WHEN ORDERING PARTS.
- 2) FOR DIFFERENT VOLTAGES OTHER THAN 120/60, REPLACE SOLENOID COIL WITH COIL