


|     |     |           |  |
|-----|-----|-----------|--|
| 20  | 1   | V-21-SS   | SCREW, 1/4-20 X 3/16, SOCKET SET, CUP POINT, 18-8 SS                       |
| 19  | 1   | DS3-1     | SPRING, DETENT, STAINLESS, 1/4" & 3/8" VALVE. LEE SPRING # LC 0298 0 S.    |
| 18  | 1   | V-14      | BALL, CHROME STEEL 3/16 DIA, GRADE 25, FOR DETENT                          |
| 17  | 1   | V-607     | O-RING, VITON, 75 DURO, 14MM X 1MM, IP67 NUT SEAL                          |
| 16  | 2   | V-606     | O-RING, VITON, 75 DURO, 8MM X 1MM, IP67 STEM SEAL                          |
| 15  | 1   | EMG3      | GASKET - END MOUNT SOLENOID, BUNA-N, 1/4" & 3/8" VALVES                    |
| 14  | 1   | V-19-SS   | PLUG, 1/8-27 NPT, 7/8 TAPER, FLUSH SEAL, SOCKET PIPE PLUG, STAINLESS       |
| 13  | 1   | V-556     | NUT, SOLENOID, TOP EXHAUST, KNURLED  |
| 12  | 1   | V-600-1   | COIL - 1/2 NPTF HUB 120V 50/60HZ, NASS P/N 0561 44.1-00/4984               |
| 11  | 4   | V-584-SS  | SCREW, 10-24 X 1, BUTTON HEAD SOCKET CAP, 18-8 OR 303 SS                   |
| 10  | 1   | SEC3-7    | PLATE, RE-INFORCEMENT, SOLENOID, STAMPED, 304 STAINLESS                    |
| 9   | 1   | V-550-1   | SOL OPER, END MOUNT, NON-LOCKING O'RIDE                                    |
| 8   | 1   | S3R       | SPOOL - SOLID, STANDARD, 2 POS, CLSD CTR, 1/4" & 3/8" VALVE                |
| 7   | 1   | PBS3-13   | STUD - POS. A & C. DETENT, SOLENOID OPERATOR, STAINLESS, 1/4" & 3/8" VALVE |
| 6   | 1   | PEC3-11   | END CAP, PILOT, STAINLESS STEEL, 1/4" & 3/8" VALVE                         |
| 5   | 4   | V-614-SS  | SCREW, 10-24 X 1-3/4", SOCKET HEAD CAP, 18-8 SS                            |
| 4   | 1   | PEC3-18-Z | END CAP, SPACER, DETENT, SOLENOID, 360 BRASS, 1/4" & 3/8" VALVES           |
| 3   | 2   | ECG3      | GASKET - END CAP, 1/4" & 3/8" VALVE  |
| 2   | 6   | V-39      | O-RING, VITON, STD BODY, 1/4" & 3/8" VALVES                                |
| 1   | 1   | ZB2-1     | BODY - BRASS, UPPER PILOTS (BUTTON BLEEDER), 1/4" SIDE PORT VALVE          |
| FLG | QTY | PART NO   | DESCRIPTION  |

- NOTES:  
 1) ALWAYS GIVE VALVE MODEL AND PART NUMBER WHEN ORDERING PARTS.  
 2) FOR DIFFERENT VOLTAGES OTHER THAN 120/60, REPLACE SOLENOID COIL WITH COIL LISTED IN TABLE BELOW.  
 3) LUBRICATE DETENT BALL, SPRING AND STUD.



| COIL VOLTAGES  |              |
|----------------|--------------|
| PART NO        | REPLACE COIL |
| ZESR2JQ 240/60 | V-600-4      |
| ZESR2JQ 24VDC  | V-600-3      |
| ZESR2JQ 12VDC  | V-600-2      |

|   |  |  |                   |
|---|--|--|-------------------|
| LIMITS ON DIMENSIONS UNLESS OTHERWISE SPECIFIED   |  | 2-PL DECIMAL ± .01<br>3-PL DECIMAL ± .005<br>FRACTIONAL ± 1/64<br>ANGULAR ± 1/2° |                   |
| DRAWN: RMckenna   |  | DATE: 5/17/2016  | CHECKED: KWaite   |
| SCALE: 1 : 1  |  | SHEET: 1 OF 1  | RELEASED: HWomack |
| TITLE:<br><b>1/4" SIDE PORT, SNGL SOL, 2 POS, DETENT, PILOT RTRN, BRASS &amp; SS, MOLD-OVER, 120/60</b> |  | PART NO.:<br><b>ZESR2JQ</b>  | REV.:             |



THE INFORMATION CONTAINED WITHIN THIS DOCUMENT IS PROPRIETARY TO AAA PRODUCTS AND MAY NOT BE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT