


|     |     |            |  |
|-----|-----|------------|--|
| 23  | 1   | ZNSPK-2    | KIT - SUBPLATE MOUNTING, BRASS NAMUR, (2 EA V-618-SS SCREW, 2 EA V-565 O-RING) |
| 22  | 1   | V-21-SS    | SCREW, 1/4-20 X 3/16, SOCKET SET, CUP POINT, 18-8 SS                           |
| 21  | 1   | DS3-1      | SPRING, DETENT, STAINLESS, 1/4" & 3/8" VALVE. LEE SPRING # LC 0298 0 S.        |
| 20  | 1   | V-14       | BALL, CHROME STEEL 3/16 DIA, GRADE 25, FOR DETENT                              |
| 19  | 1   | V-548      | O-RING, BUNA-N, 70 DURO, 6MM X 1MM, NAMUR PLUG                                 |
| 18  | 1   | V-547      | PLUG, 360 HALF HARD BRASS, NAMUR VALVE   |
| 15  | 1   | PEC3-18-Z  | END CAP, SPACER, DETENT, SOLENOID, 360 BRASS, 1/4" & 3/8" VALVES               |
| 14  | 1   | EMG3       | GASKET - END MOUNT SOLENOID, BUNA-N, 1/4" & 3/8" VALVES                        |
| 13  | 1   | V-19-SS    | PLUG, SOCKET PIPE 1/8"-27 NPT, 7/8 TAPER, PLAIN, FLUSH SEAL, STAINLESS STEEL   |
| 12  | 1   | V-567W     | E SERIES SINTERED BRONZE MUFFLER, DUST EXCLUDER, V-613 LOCK WASHER             |
| 11  | 1   | V-603-1    | COIL HI-TEMP. 8-30T 120/60. NASS # 0558 55.1-00/7121.                          |
| 10  | 4   | V-585-SS   | SCREW, 10-24 X 2-1/8, SOCKET BUTTON HEAD, 18-8 STAINLESS                       |
| 9   | 1   | SEC3-7     | PLATE, RE-INFORCEMENT, SOLENOID, STAMPED, 304 STAINLESS                        |
| 8   | 1   | V-550-1    | SOL OPER, END MOUNT, NON-LOCKING O-RIDE  |
| 7   | 1   | S3R        | SPOOL - SOLID, STANDARD, 2 POS, CLSD CTR, 1/4" & 3/8" VALVE                    |
| 6   | 1   | PBS3-13-SS | STUD - POS. A & C. DETENT, STAINLESS STEEL, 1/4" & 3/8" VALVE                  |
| 5   | 1   | PEC3-11    | END CAP, PILOT, STAINLESS STEEL, 1/4" & 3/8" VALVE                             |
| 4   | 4   | V-38-SS    | SCREW, 10-24 X 3/4, SOCKET HEAD CAP, 18-8 SS                                   |
| 3   | 2   | ECG3       | GASKET - END CAP, 1/4" & 3/8" VALVE  |
| 2   | 6   | V-39       | O-RING, VITON, STD BODY, 1/4" & 3/8" VALVES                                    |
| 1   | 1   | Z2-11      | BODY - BRASS, UPPER PILOTS (BUTTON BLEEDER), 1/4" NAMUR                        |
| FLG | QTY | PART NO    | DESCRIPTION  |

- NOTES:  
 1) ALWAYS GIVE VALVE MODEL AND PART NUMBER WHEN ORDERING PARTS.  
 2) FOR DIFFERENT VOLTAGES OTHER THAN 120/60, REPLACE SOLENOID COIL WITH COIL LISTED IN TABLE BELOW.  
 3) LUBRICATE DETENT BALL, SPRING AND STUD.



| COIL VOLTAGES  |              |
|----------------|--------------|
| PART NO        | REPLACE COIL |
| ZNSR2HLQ 12VDC | V-603-2      |

|  |                 |  |                 |  |
|--|-----------------|--|-----------------|--|
| LIMITS ON DIMENSIONS UNLESS OTHERWISE SPECIFIED  |                 | 2-PL DECIMAL ± .01<br>3-PL DECIMAL ± .005<br>FRACTIONAL ± 1/64<br>ANGULAR ± 1/2° |                 | <b>AAA PRODUCTS INTERNATIONAL</b><br>7114 Harry Hines Blvd<br>Dallas, TX 75235 |
| DRAWN: RMckenna  | DATE: 6/17/2022 | CHECKED: KWaite  | DATE: 6/17/2022 |  |
| SCALE: 1 : 1   | SHEET: 1 OF 1   | RELEASED: HWomack  | DATE: 6/17/2022 |  |
| TITLE:<br>1/4" NAMUR, SNGL SOL, 2 POS, DTNT, PLT RTRN, H-TEMP, 120/60, BR & SS, DUST EXLDR |                 | PART NO.:<br>ZNSR2HLQ  |                 | REV.:  |

THE INFORMATION CONTAINED WITHIN THIS DOCUMENT IS PROPRIETARY TO AAA PRODUCTS AND MAY NOT BE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT